



Bearing No. 6313

D	140 mm
d	65 mm
B	33 mm
C	33 mm
r	2.1
Z_	8
D_	140
ra	2
C0	60
fo	13.2
B_	33
DI_	78.688
SRI	12.32
SRE	12.32
D_a	129
DA_	23.812
DE_	126.312
SREX	0.04
SREN	-0.04
SBRG	3
KBRG	6101
mass	2.11
Bore	2.559 Inch 65 Millimeter
SRIX	0.04
SRIN	-0.04
Noun	Bearing
yobi	6313
SDM_	102.5
bomp	0

Weight	2,11 Kg
C_conv	92500
LangID	1
da min	76
r min.	2,1 mm
ALPHA_	0
UNSPSC	31171504
da max	85,5 mm
GRS rpm	4800
Oil rpm	6000
hidYobi	6313
ra max.	2 mm
Da max.	129 mm
da min.	76 mm
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Size (mm)	65x140x33
Inventory	4.0
Enclosure	Open
Snap Ring	No
Prod_Type3	DGBB_SR_OT
Width (mm)	33
bore type:	Round
Weight / LBS	2.16
Product Group	B00308
Cage Material	Steel
Inch - Metric	Metric
closure type:	Open
Bearing number	6313
Keyword String	Ball
overall width:	33 mm
bore diameter:	65 mm

Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Long Description	65MM Bore; 140MM Outside Diameter; 33MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Outside Diameter	5.512 Inch 140 Millimeter
Manufacturer URL	http://www.nskamericas.com
Outer Race Width	1.299 Inch 33 Millimeter
outside diameter:	140 mm
Manufacturer Name	NSK
Weight / Kilogram	2.15
Bore Diameter (mm)	65
Internal Clearance	C0-Medium
internal clearance:	Normal Clearance
Outer Diameter (mm)	140
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
(Oil) Lubrication Speed	6 000 r/min
Manufacturer Item Number	6313
manufacturer upc number:	029176017322
Internal Special Features	No
(Grease) Lubrication Speed	4 800 r/min
Basic static load rating (C0)	60 kN
Basic dynamic load	92,5 kN

rating (C)	
Maximum Capacity / Filling Slot	No