



Bearing No. 6913

D	90 mm
d	65 mm
B	13 mm
C	13 mm
r	1
Z_	19
C0	16.1
ra	1
fo	16.6
D_	90
B_	13
DI_	70.356
SRI	3.7
DE_	84.644
DA_	7.144
SRE	3.7
D_a	85
KBRG	6101
SRIX	0.02
Noun	Bearing
yobi	6913
SDM_	77.5
bomp	0
SRIN	-0.02
mass	0.218
SREX	0.02
Bore	2.559 Inch 65 Millimeter
SBRG	19
SREN	-0.02

ALPHA_	0
UNSPSC	31171504
da max	71,5 mm
LangID	1
r min.	1 mm
C_conv	17400
Weight	0,218 Kg
da min	70
GRS rpm	7100
Oil rpm	8500
hidYobi	6913
da min.	70 mm
Da max.	85 mm
ra max.	1 mm
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Inventory	0.0
Snap Ring	No
Size (mm)	65x90x13
Enclosure	Open
bore type:	Round
Prod_Type3	DGBB_SR_OT
Width (mm)	13
Weight / LBS	0.21
maximum rpm:	8500 rpm
Product Group	B00308
closure type:	Open
Cage Material	Steel
Inch - Metric	Metric
Bearing number	6913
bore diameter:	65 mm
cage material:	Steel Cage

overall width:	13 mm
Keyword String	Ball
finish/coating:	Uncoated
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outside Diameter	3.543 Inch 90 Millimeter
Manufacturer URL	http://www.nskamericas.com
Long Description	65MM Bore; 90MM Outside Diameter; 13MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Outer Race Width	0.512 Inch 13 Millimeter
Weight / Kilogram	0.21
Manufacturer Name	NSK
precision rating:	ABEC1, P0
outside diameter:	90 mm
Internal Clearance	C0-Medium
Bore Diameter (mm)	65
snap ring included:	Without Snap Ring
Outer Diameter (mm)	90
internal clearance:	C0
Minimum Buy Quantity	N/A
row type & fill slot:	Single Row Non-Fill Slot
dynamic load capacity:	17400 N
Harmonized Tariff Code	8482.10.50.68
(Oil) Lubrication Speed	8 500 r/min
Manufacturer Item Number	6913
Internal Special	No

Features	
(Grease) Lubrication Speed	7 100 r/min
Basic static load rating (C0)	16,1 kN
Basic dynamic load rating (C)	17,4 kN
Maximum Capacity / Filling Slot	No