



Bearing No. 6913DDU

| | |
|------|-------------------------------|
| r | 1 |
| d | 65 mm |
| D | 90 mm |
| B | 13 mm |
| C | 13 mm |
| D_ | 90 |
| C0 | 16.1 |
| Z_ | 19 |
| ra | 1 |
| fo | 16.6 |
| B_ | 13 |
| DI_ | 70.356 |
| SRI | 3.7 |
| SRE | 3.7 |
| DE_ | 84.644 |
| DA_ | 7.144 |
| D_a | 85 |
| KBRG | 6161 |
| SBRG | 19 |
| SRIN | -0.02 |
| bomp | 0 |
| SREX | 0.02 |
| yobi | 6913DDU |
| SRIX | 0.02 |
| Bore | 2.559 Inch 65 Millimeter |
| SDM_ | 77.5 |
| SREN | -0.02 |
| mass | 0.218 |
| Noun | Bearing |
| | |

| | |
|------------------|---------------------------|
| LangID | 1 |
| UNSPSC | 31171504 |
| da min | 70 |
| ALPHA_ | 0 |
| r min. | 1 mm |
| Weight | 0,218 Kg |
| C_conv | 17400 |
| da max | 71,5 mm |
| Da max. | 85 mm |
| ra max. | 1 mm |
| GRS rpm | 4000 |
| da min. | 70 mm |
| hidYobi | 6913DDU |
| Category | Single Row Ball Bearing |
| hidTable | ecat_NSRDGB |
| Size (mm) | 65x90x13 |
| Enclosure | 2 Seals |
| Snap Ring | No |
| Inventory | 0.0 |
| Width (mm) | 13 |
| Prod_Type3 | DGBB_SR_DD |
| Weight / LBS | 0.4807 |
| Inch - Metric | Metric |
| Product Group | B00308 |
| Cage Material | Steel |
| Bearing number | 6913DDU |
| Keyword String | Ball |
| Other Features | Deep Groove Rubber Seal |
| Enclosure Type | Contact Seal |
| Precision Class | ABEC 1 ISO P0 |
| Rolling Element | Ball Bearing |
| Outer Race Width | 0.512 Inch 13 |

| | |
|---------------------------------|---|
| | Millimeter |
| Outside Diameter | 3.543 Inch 90 Millimeter |
| Long Description | 65MM Bore; 90MM Outside Diameter; 13MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage; |
| Manufacturer URL | http://www.nskamericas.com |
| Inner Race Width | 0 Inch 0 Millimeter |
| Manufacturer Name | NSK |
| Weight / Kilogram | 0.21 |
| Internal Clearance | C0-Medium |
| Bore Diameter (mm) | 65 |
| Outer Diameter (mm) | 90 |
| Minimum Buy Quantity | N/A |
| Harmonized Tariff Code | 8482.10.50.68 |
| Manufacturer Item Number | 6913DDU |
| Internal Special Features | No |
| (Grease) Lubrication Speed | 4 000 r/min |
| Basic static load rating (C0) | 16,1 kN |
| Basic dynamic load rating (C) | 17,4 kN |
| Maximum Capacity / Filling Slot | No |