



Bearing No. 6911DDU

r	1
d	55 mm
D	80 mm
B	13 mm
C	13 mm
D_	80
C0	13.3
Z_	16
ra	1
fo	16.2
B_	13
DI_	60.356
SRI	3.7
SRE	3.7
DE_	74.644
DA_	7.144
D_a	75
KBRG	6161
SBRG	19
SRIN	-0.02
bomp	0
SREX	0.02
yobi	6911DDU
SRIX	0.02
mass	0.189
SDM_	67.5
SREN	-0.02
Bore	2.165 Inch 55 Millimeter
Noun	Bearing

LangID	1
UNSPSC	31171504
da min	60
r min.	1 mm
Weight	0,189 Kg
ALPHA_	0
C_conv	16000
da max	61,5 mm
GRS rpm	4500
Da max.	75 mm
ra max.	1 mm
da min.	60 mm
hidYobi	6911DDU
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Size (mm)	55x80x13
Enclosure	2 Seals
Snap Ring	No
Inventory	0.0
Width (mm)	13
Prod_Type3	DGBB_SR_DD
Weight / LBS	0.4167
Inch - Metric	Metric
Product Group	B00308
Cage Material	Steel
Bearing number	6911DDU
Keyword String	Ball
Other Features	Deep Groove Rubber Seal
Enclosure Type	Contact Seal
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outside Diameter	3.15 Inch 80 Millimeter

Outer Race Width	0.512 Inch 13 Millimeter
Long Description	55MM Bore; 80MM Outside Diameter; 13MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage;
Manufacturer URL	http://www.nskamericas.com
Inner Race Width	0 Inch 0 Millimeter
Manufacturer Name	NSK
Weight / Kilogram	0.18
Internal Clearance	C0-Medium
Bore Diameter (mm)	55
Outer Diameter (mm)	80
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6911DDU
Internal Special Features	No
(Grease) Lubrication Speed	4 500 r/min
Basic static load rating (C0)	13,3 kN
Basic dynamic load rating (C)	16 kN
Maximum Capacity / Filling Slot	No