



Bearing No. 6313DDU

r	2.1
d	65 mm
D	140 mm
B	33 mm
C	33 mm
fo	13.2
D_	140
B_	33
ra	2
Z_	8
C0	60
DI_	78.688
SRE	12.32
D_a	129
DE_	126.312
SRI	12.32
DA_	23.812
SREN	-0.04
Bore	2.559 Inch 65 Millimeter
SRIN	-0.04
bomp	0
SRIX	0.04
yobi	6313DDU
mass	2.11
SDM_	102.5
KBRG	6161
SREX	0.04
SBRG	3
Noun	Bearing

da max	85,5 mm
LangID	1
r min.	2,1 mm
da min	76
ALPHA_	0
C_conv	92500
UNSPSC	31171504
Weight	2,11 Kg
ra max.	2 mm
da min.	76 mm
hidYobi	6313DDU
GRS rpm	3400
Da max.	129 mm
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Snap Ring	No
Enclosure	2 Seals
Size (mm)	65x140x33
Inventory	0.0
Prod_Type3	DGBB_SR_DD
Width (mm)	33
Weight / LBS	4.6526
Product Group	B00308
Inch - Metric	Metric
Cage Material	Steel
Bearing number	6313DDU
Enclosure Type	Contact Seal
Other Features	Deep Groove Rubber Seal
Keyword String	Ball
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Inner Race Width	0 Inch 0 Millimeter

Outside Diameter	5.512 Inch 140 Millimeter
Long Description	65MM Bore; 140MM Outside Diameter; 33MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage;
Manufacturer URL	http://www.nskamericas.com
Outer Race Width	1.299 Inch 33 Millimeter
Weight / Kilogram	2.2
Manufacturer Name	NSK
Internal Clearance	C0-Medium
Bore Diameter (mm)	65
Outer Diameter (mm)	140
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Internal Special Features	No
(Grease) Lubrication Speed	3 400 r/min
Basic dynamic load rating (C)	92,5 kN
Basic static load rating (C0)	60 kN
Maximum Capacity / Filling Slot	No