



**Bearing No. 6313LLB**

C	33 mm
d	65 mm
D	140 mm
B	33 mm
Bore	2.559 Inch   65 Millimeter
Noun	Bearing
Weight	2,08 Kg
r min.	2,1 mm
da max	86 mm
UNSPSC	31171504
da min.	76 mm
Da max.	129 mm
ra max.	2 mm
Category	Single Row Ball Bearing
Size (mm)	65x140x33
Snap Ring	No
Inventory	0.0
Enclosure	2 Seals
Width (mm)	33
bore type:	Round
Weight / LBS	4.885
Inch - Metric	Metric
closure type:	Double Sealed
Product Group	B00308
Cage Material	Steel
bore diameter:	65 mm
Keyword String	Ball
overall width:	33 mm
cage material:	Steel

fillet radius:	2.1 mm
Other Features	Deep Groove   Non-Friction Nitrile Rubber Seal   Shell Alvania Prelubricated
Bearing number	6313LLB
Enclosure Type	Non-Contact Seal
finish/coating:	Uncoated
Rolling Element	Ball Bearing
Precision Class	ABEC 1   ISO P0
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Outside Diameter	5.512 Inch   140 Millimeter
Long Description	65MM Bore; 140MM Outside Diameter; 33MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage;
Outer Race Width	1.299 Inch   33 Millimeter
Inner Race Width	0 Inch   0 Millimeter
Manufacturer Name	NTN
bearing material:	High Carbon Chrome Steel
precision rating:	ISO Class 0
Weight / Kilogram	0
inner ring width:	33 mm
outer ring width:	33 mm
outside diameter:	140 mm
Bore Diameter (mm)	65
Internal Clearance	C0-Medium

snap ring included:	Without Snap Ring
Outer Diameter (mm)	140
internal clearance:	CN
Minimum Buy Quantity	N/A
static load capacity:	60000 N
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	4900 rpm
Harmonized Tariff Code	8482.10.50.68
dynamic load capacity:	92500 N
Internal Special Features	No
(Grease) Lubrication Speed	4 900 r/min
manufacturer product page:	<a href="#">Click here</a>
operating temperature range:	-40 to 120 °C
Basic static load rating (C0)	60 kN
Basic dynamic load rating (C)	92,5 kN
Maximum Capacity / Filling Slot	No