



Bearing No. 6313VV

D	140 mm
d	65 mm
B	33 mm
C	33 mm
r	2.1
C0	60
fo	13.2
ra	2
D_	140
B_	33
Z_	8
DI_	78.688
D_a	129
DE_	126.312
SRI	12.32
DA_	23.812
SRE	12.32
Noun	Bearing
SREN	-0.04
SDM_	102.5
SRIN	-0.04
yobi	6313VV
mass	2.11
Bore	2.559 Inch 65 Millimeter
bomp	0
SREX	0.04
SBRG	3
SRIX	0.04
KBRG	6151

UNSPSC	31171504
ALPHA_	0
LangID	1
r min.	2,1 mm
da max	85,5 mm
da min	76
Weight	2,11 Kg
C_conv	92500
GRS rpm	4800
hidYobi	6313VV
da min.	76 mm
Da max.	129 mm
ra max.	2 mm
hidTable	ecat_NSRDGB
Category	Single Row Ball Bearing
Inventory	0.0
Snap Ring	No
Size (mm)	65x140x33
Enclosure	2 Seals
Prod_Type3	DGBB_SR_VV
bore type:	Round
Width (mm)	33
Weight / LBS	2.25
Cage Material	Steel
Product Group	B00308
closure type:	Two Non-Contact Seals
Inch - Metric	Metric
Bearing number	6313VV
bore diameter:	65 mm
overall width:	33 mm
Keyword String	Ball
Enclosure Type	Non-Contact Seal

Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Outer Race Width	1.299 Inch 33 Millimeter
Long Description	65MM Bore; 140MM Outside Diameter; 33MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Outside Diameter	5.512 Inch 140 Millimeter
Manufacturer URL	http://www.nskamericas.com
Weight / Kilogram	2.25
bearing material:	Steel
outside diameter:	140 mm
Manufacturer Name	NSK
maximum rpm (oil):	6700 rpm
Bore Diameter (mm)	65
Internal Clearance	C0-Medium
Outer Diameter (mm)	140
snap ring included:	Without Snap Ring
internal clearance:	C0
Minimum Buy Quantity	N/A
maximum rpm (grease):	5600 rpm
static load capacity:	13400 lbs
row type & fill slot:	Single Row Non-Fill Slot
manufacturer catalog:	Click here
dynamic load capacity:	21900 lbs
Harmonized Tariff Code	8482.10.50.68
manufacturer upc number:	029176017346
Manufacturer Item	6313VV

Number	
Internal Special Features	No
(Grease) Lubrication Speed	4 800 r/min
Basic static load rating (C0)	60 kN
Basic dynamic load rating (C)	92,5 kN
Maximum Capacity / Filling Slot	No