



Bearing No. 6910N

a	1,7 mm
r	0.6
d	50 mm
D	72 mm
B	12 mm
C	12 mm
b	0,95 mm
fo	16.1
B_	12
ra	0.6
C0	11.7
D1	70,7 mm
D_	72
Z_	16
rn	0,5 mm
ro	0.25
DE_	67.747
SRI	3.49
D_a	68
DA_	6.747
SRE	3.49
DI_	54.253
yobi	6910N
mass	0.135
SBRG	19
bomp	0
KBRG	6101
SREX	0.02
SREN	-0.02
SRIN	-0.02

SDM_	61
SRIX	0.02
ALPHA_	0
r min.	0,6 mm
C_conv	14500
da max	55 mm
da min	54
Weight	0,135 Kg
LangID	1
ra max.	0,6 mm
Da max.	68 mm
Oil rpm	11000
da min.	54 mm
r0 max.	0,25 mm
hidYobi	6910N
GRS rpm	9000
hidTable	ecat_NSRDGB
Size (mm)	50x72x12
Prod_Type3	DGBB_SR_N_OT
Width (mm)	12
Bearing number	6910N
Bore Diameter (mm)	50
Outer Diameter (mm)	72
(Oil) Lubrication Speed	11 000 r/min
(Grease) Lubrication Speed	9 000 r/min
Basic dynamic load rating (C)	14,5 kN
Basic static load rating (C0)	11,7 kN