



Bearing No. 6314N

a	4,9 mm
r	2.1
d	70 mm
D	150 mm
B	35 mm
C	35 mm
b	3,1 mm
fo	13.2
B_	35
ra	2
C0	68
D1	145,24 mm
D_	150
Z_	8
rn	0,5 mm
ro	0.6
DE_	135.4
SRI	13.14
D_a	139
DA_	25.4
SRE	13.14
DI_	84.6
yobi	6314N
mass	2.57
SBRG	3
bomp	0
KBRG	6101
SREX	0.05
SREN	-0.05
SRIN	-0.05

SDM_	110
SRIX	0.05
ALPHA_	0
r min.	2,1 mm
C_conv	104000
da max	92 mm
da min	81
Weight	2,57 Kg
LangID	1
ra max.	2 mm
Da max.	139 mm
Oil rpm	5300
da min.	81 mm
r0 max.	0,6 mm
hidYobi	6314N
GRS rpm	4500
hidTable	ecat_NSRDGB
Size (mm)	70x150x35
Prod_Type3	DGBB_SR_N_OT
Width (mm)	35
Bearing number	6314N
Bore Diameter (mm)	70
Outer Diameter (mm)	150
(Oil) Lubrication Speed	5 300 r/min
(Grease) Lubrication Speed	4 500 r/min
Basic dynamic load rating (C)	104 kN
Basic static load rating (C0)	68 kN