



Bearing No. 6908N

a	1,7 mm
r	0.6
d	40 mm
D	62 mm
B	12 mm
C	12 mm
b	0,95 mm
fo	15.7
B_	12
ra	0.6
C0	10
D1	60,7 mm
D_	62
Z_	14
rn	0,5 mm
ro	0.25
DE_	58.747
SRI	3.41
D_a	58
DA_	6.747
SRE	3.58
DI_	45.253
yobi	6908N
mass	0.112
SBRG	19
bomp	0
KBRG	6101
SREX	0.04
SREN	0
SRIN	0

SDM_	52
SRIX	0.02
ALPHA_	0
r min.	0,6 mm
C_conv	13700
da max	46 mm
da min	44
Weight	0,112 Kg
LangID	1
ra max.	0,6 mm
Da max.	58 mm
Oil rpm	13000
da min.	44 mm
r0 max.	0,25 mm
hidYobi	6908N
GRS rpm	11000
hidTable	ecat_NSRDGB
Size (mm)	40x62x12
Prod_Type3	DGBB_SR_N_OT
Width (mm)	12
Bearing number	6908N
Bore Diameter (mm)	40
Outer Diameter (mm)	62
(Oil) Lubrication Speed	13 000 r/min
(Grease) Lubrication Speed	11 000 r/min
Basic dynamic load rating (C)	13,7 kN
Basic static load rating (C0)	10 kN