



Bearing No. 6908NR

f	0,85 mm
r	0.6
d	40 mm
D	62 mm
B	12 mm
C	12 mm
a	1,7 mm
b	0,95 mm
D2	64,8 mm
B_	12
Cy	2.3
ra	0.6
C0	10
fo	15.7
D_	62
D1	60,7 mm
rn	0,5 mm
Z_	14
Dx	65.5
ro	0.25
DE_	58.747
DA_	6.747
SRI	3.41
D_a	58
SRE	3.58
DI_	45.253
SRIN	0
yobi	6908NR
SBRG	19
bomp	0

SREX	0.04
KBRG	6101
SREN	0
SDM_	52
SRIX	0.02
mass	0.112
C_conv	13700
r min.	0,6 mm
da max	46 mm
ALPHA_	0
Weight	0,112 Kg
da min	44
LangID	1
GRS rpm	11000
Da max.	58 mm
hidYobi	6908NR
Oil rpm	13000
da min.	44 mm
r0 max.	0,25 mm
ra max.	0,6 mm
hidTable	ecat_NSRDGB
Size (mm)	40x62x12
Prod_Type3	DGBB_SR_NR_OT
Width (mm)	12
Bearing number	6908NR
Bore Diameter (mm)	40
Outer Diameter (mm)	62
(Oil) Lubrication Speed	13 000 r/min
(Grease) Lubrication Speed	11 000 r/min
Basic dynamic load rating (C)	13,7 kN
Basic static load rating	10 kN

(C0)	
------	--