



Bearing No. 6908

D	62 mm
d	40 mm
B	12 mm
C	12 mm
f0	15.6
Cu	0.570
Cr	17.1
C0r	9.95
Bore	1.575 Inch 40 Millimeter
Noun	Bearing
UNSPSC	31171504
Weight	0,112 Kg
r(min)	0.6
r min.	0,6 mm
da min.	44 mm
ra(max)	0.6
Da max.	58 mm
Da(max)	58
da(min)	44
ra max.	0,6 mm
Category	Single Row Ball Bearing
Oil lub.	13000
Inventory	0.0
Enclosure	Open
Size (mm)	40x62x12
Snap Ring	No
Width (mm)	12
Grease lub.	11000
Bearing No.	6908

Weight / LBS	0.262
Product Group	B00308
Cage Material	Steel
Inch - Metric	Metric
Keyword String	Ball
Bearing number	6908
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outside Diameter	2.441 Inch 62 Millimeter
Long Description	40MM Bore; 62MM Outside Diameter; 12MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Outer Race Width	0.472 Inch 12 Millimeter
(Refer.)Mass(kg)	0.112
Manufacturer URL	http://www.koyousa.com
Weight / Kilogram	0.119
Manufacturer Name	KOYO
Internal Clearance	C0-Medium
Bore Diameter (mm)	40
Outer Diameter (mm)	62
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
(Oil) Lubrication Speed	13000 r/min
Manufacturer Item Number	6908
Internal Special Features	No
(Grease) Lubrication Speed	11000 r/min

Basic static load rating (C0)	9,95 kN
Basic dynamic load rating (C)	13,7 kN
Maximum Capacity / Filling Slot	No