



Bearing No. 6908

D	62 mm
d	40 mm
B	12 mm
C	12 mm
r	0.6
Z_	14
C0	10
ra	0.6
fo	15.7
D_	62
B_	12
DI_	45.253
SRI	3.41
DE_	58.747
DA_	6.747
SRE	3.58
D_a	58
Bore	1.575 Inch 40 Millimeter
SRIX	0.02
Noun	Bearing
yobi	6908
SDM_	52
bomp	0
SRIN	0
mass	0.112
SREX	0.04
SBRG	19
KBRG	6101
SREN	0

ALPHA_	0
UNSPSC	31171504
da max	46 mm
LangID	1
r min.	0,6 mm
C_conv	13700
Weight	0,112 Kg
da min	44
GRS rpm	11000
Oil rpm	13000
hidYobi	6908
da min.	44 mm
Da max.	58 mm
ra max.	0,6 mm
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Inventory	0.0
Snap Ring	No
Size (mm)	40x62x12
Enclosure	Open
bore type:	Round
Prod_Type3	DGBB_SR_OT
Width (mm)	12
Weight / LBS	0.11
maximum rpm:	13000 rpm
Product Group	B00308
closure type:	Open
Cage Material	Steel
Inch - Metric	Metric
Bearing number	6908
bore diameter:	40 mm
cage material:	Steel Cage

overall width:	12 mm
Keyword String	Ball
finish/coating:	Uncoated
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outer Race Width	0.472 Inch 12 Millimeter
Manufacturer URL	http://www.nskamericas.com
Long Description	40MM Bore; 62MM Outside Diameter; 12MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Outside Diameter	2.441 Inch 62 Millimeter
Weight / Kilogram	0.05
Manufacturer Name	NSK
precision rating:	ABEC1, P0
outside diameter:	62 mm
Internal Clearance	C0-Medium
Bore Diameter (mm)	40
snap ring included:	Without Snap Ring
Outer Diameter (mm)	62
internal clearance:	C0
Minimum Buy Quantity	N/A
row type & fill slot:	Single Row Non-Fill Slot
dynamic load capacity:	13700 N
Harmonized Tariff Code	8482.10.50.68
(Oil) Lubrication Speed	13 000 r/min
Manufacturer Item Number	6908
Internal Special	No

Features	
(Grease) Lubrication Speed	11 000 r/min
Basic static load rating (C0)	10 kN
Basic dynamic load rating (C)	13,7 kN
Maximum Capacity / Filling Slot	No