



Bearing No. 6908DDU

r	0.6
d	40 mm
D	62 mm
B	12 mm
C	12 mm
D_	62
Z_	14
B_	12
ra	0.6
fo	15.7
C0	10
DI_	45.253
DE_	58.747
DA_	6.747
D_a	58
SRE	3.58
SRI	3.41
Noun	Bearing
SRIN	0
bomp	0
Bore	1.575 Inch 40 Millimeter
SREN	0
mass	0.112
SRIX	0.02
SREX	0.04
SBRG	19
yobi	6908DDU
KBRG	6161
SDM_	52

UNSPSC	31171504
da min	44
C_conv	13700
LangID	1
da max	46 mm
ALPHA_	0
r min.	0,6 mm
Weight	0,112 Kg
da min.	44 mm
GRS rpm	6300
Da max.	58 mm
ra max.	0,6 mm
hidYobi	6908DDU
hidTable	ecat_NSRDGB
Category	Single Row Ball Bearing
Enclosure	2 Seals
Snap Ring	No
Inventory	0.0
Size (mm)	40x62x12
Width (mm)	12
bore type:	Round
Prod_Type3	DGBB_SR_DD
Weight / LBS	1.575
closure type:	Double Sealed
Product Group	B00308
Inch - Metric	Metric
Cage Material	Steel
Bearing number	6908DDU
Keyword String	Ball
bore diameter:	40 mm
overall width:	12 mm
Enclosure Type	Contact Seal

Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outside Diameter	2.441 Inch 62 Millimeter
Long Description	40MM Bore; 62MM Outside Diameter; 12MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer URL	http://www.nskamericas.com
Outer Race Width	0.472 Inch 12 Millimeter
outside diameter:	62 mm
Weight / Kilogram	0.11
Manufacturer Name	NSK
Internal Clearance	C0-Medium
Bore Diameter (mm)	40
Outer Diameter (mm)	62
internal clearance:	Normal Clearance
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
manufacturer upc number:	029176066719
Internal Special Features	No
(Grease) Lubrication Speed	6 300 r/min
Basic static load rating (C0)	10 kN
Basic dynamic load rating (C)	13,7 kN
Maximum Capacity / Filling Slot	No

