



Bearing No. 6907VV

D	55 mm
d	35 mm
B	10 mm
C	10 mm
r	0.6
C0	7.25
fo	15.5
ra	0.6
D_	55
B_	10
Z_	13
DI_	38.5
D_a	51
DE_	50.5
SRI	3.1
DA_	6
SRE	3.1
Noun	Bearing
SREN	-0.015
SDM_	44.5
SRIN	-0.015
yobi	6907VV
mass	0.075
Bore	1.378 Inch   35 Millimeter
bomp	0
SREX	0.015
SBRG	19
SRIX	0.015
KBRG	6151

UNSPSC	31171504
ALPHA_	0
LangID	1
r min.	0,6 mm
da max	39 mm
da min	39
Weight	0,075 Kg
C_conv	10600
GRS rpm	12000
hidYobi	6907VV
da min.	39 mm
Da max.	51 mm
ra max.	0,6 mm
hidTable	ecat_NSRDGB
Category	Single Row Ball Bearing
Inventory	0.0
Snap Ring	No
Size (mm)	35x55x10
Enclosure	2 Seals
Prod_Type3	DGBB_SR_VV
bore type:	Round
Width (mm)	10
Weight / LBS	0.075
Cage Material	Steel
Product Group	B00308
closure type:	Two Non-Contact Seals
Inch - Metric	Metric
Bearing number	6907VV
bore diameter:	35 mm
overall width:	10 mm
Keyword String	Ball
Enclosure Type	Non-Contact Seal

Rolling Element	Ball Bearing
Precision Class	ABEC 1   ISO P0
Outside Diameter	2.165 Inch   55 Millimeter
Long Description	35MM Bore; 55MM Outside Diameter; 10MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Outer Race Width	0.394 Inch   10 Millimeter
Manufacturer URL	<a href="http://www.nskamericas.com">http://www.nskamericas.com</a>
Weight / Kilogram	0.03
bearing material:	Steel
outside diameter:	55 mm
Manufacturer Name	NSK
maximum rpm (oil):	15000 rpm
Bore Diameter (mm)	35
Internal Clearance	C0-Medium
Outer Diameter (mm)	55
snap ring included:	Without Snap Ring
internal clearance:	C0
Minimum Buy Quantity	N/A
maximum rpm (grease):	12000 rpm
static load capacity:	1630 lbs
row type & fill slot:	Single Row Non-Fill Slot
manufacturer catalog:	<a href="#">Click here</a>
dynamic load capacity:	2380 lbs
Harmonized Tariff Code	8482.10.50.68
manufacturer upc number:	029176026812
Manufacturer Item	6907VV

Number	
Internal Special Features	No
(Grease) Lubrication Speed	12 000 r/min
Basic static load rating (C0)	7,25 kN
Basic dynamic load rating (C)	10,6 kN
Maximum Capacity / Filling Slot	No