



Bearing No. 6907DDU

r	0.6
d	35 mm
D	55 mm
B	10 mm
C	10 mm
D_	55
C0	7.25
Z_	13
ra	0.6
fo	15.5
B_	10
DI_	38.5
SRI	3.1
SRE	3.1
DE_	50.5
DA_	6
D_a	51
KBRG	6161
SBRG	19
SRIN	-0.015
bomp	0
SREX	0.015
yobi	6907DDU
SRIX	0.015
Bore	1.378 Inch 35 Millimeter
SDM_	44.5
SREN	-0.015
mass	0.075
Noun	Bearing

LangID	1
UNSPSC	31171504
da min	39
ALPHA_	0
r min.	0,6 mm
Weight	0,075 Kg
C_conv	10600
da max	39 mm
Da max.	51 mm
ra max.	0,6 mm
GRS rpm	7500
da min.	39 mm
hidYobi	6907DDU
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Size (mm)	35x55x10
Enclosure	2 Seals
Snap Ring	No
Inventory	0.0
Width (mm)	10
Prod_Type3	DGBB_SR_DD
Weight / LBS	0.1654
Inch - Metric	Metric
Product Group	B00308
Cage Material	Steel
Bearing number	6907DDU
Keyword String	Ball
Other Features	Deep Groove Rubber Seal
Enclosure Type	Contact Seal
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outer Race Width	0.394 Inch 10

	Millimeter
Inner Race Width	0 Inch 0 Millimeter
Long Description	35MM Bore; 55MM Outside Diameter; 10MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage;
Manufacturer URL	http://www.nskamericas.com
Outside Diameter	2.165 Inch 55 Millimeter
Manufacturer Name	NSK
Weight / Kilogram	0.075
Internal Clearance	C0-Medium
Bore Diameter (mm)	35
Outer Diameter (mm)	55
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6907DDU
Internal Special Features	No
(Grease) Lubrication Speed	7 500 r/min
Basic static load rating (C0)	7,25 kN
Basic dynamic load rating (C)	10,6 kN
Maximum Capacity / Filling Slot	No