



Bearing No. 6315VV

D	160 mm
d	75 mm
B	37 mm
C	37 mm
r	2.1
Z_	8
B_	37
D_	160
ra	2
C0	77
fo	13.2
DI_	90.512
SRI	13.97
D_a	149
DE_	144.488
DA_	26.988
SRE	13.97
SRIN	-0.05
SBRG	3
yobi	6315VV
SDM_	117.5
SREX	0.05
KBRG	6151
bomp	0
mass	3.08
Bore	2.953 Inch 75 Millimeter
SRIX	0.05
SREN	-0.05
Noun	Bearing

ALPHA_	0
da min	86
LangID	1
r min.	2,1 mm
UNSPSC	31171504
da max	98,5 mm
C_conv	113000
Weight	3,08 Kg
ra max.	2 mm
hidYobi	6315VV
GRS rpm	4300
da min.	86 mm
Da max.	149 mm
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Snap Ring	No
Size (mm)	75x160x37
Enclosure	2 Seals
Inventory	0.0
Width (mm)	37
Prod_Type3	DGBB_SR_VV
Weight / LBS	3.05
Cage Material	Steel
Product Group	B00308
Inch - Metric	Metric
Bearing number	6315VV
Keyword String	Ball
Enclosure Type	Non-Contact Seal
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outside Diameter	6.299 Inch 160 Millimeter
Outer Race Width	1.457 Inch 37

	Millimeter
Long Description	75MM Bore; 160MM Outside Diameter; 37MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer URL	http://www.nskamericas.com
Weight / Kilogram	3.05
Manufacturer Name	NSK
Internal Clearance	C0-Medium
Bore Diameter (mm)	75
Outer Diameter (mm)	160
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6315VV
Internal Special Features	No
(Grease) Lubrication Speed	4 300 r/min
Basic static load rating (C0)	77 kN
Basic dynamic load rating (C)	113 kN
Maximum Capacity / Filling Slot	No