



Bearing No. 6906N

a	1,7 mm
r	0.3
d	30 mm
D	47 mm
B	9 mm
C	9 mm
b	0,95 mm
fo	15.8
B_	9
ra	0.3
C0	5
D1	45,7 mm
D_	47
Z_	14
rn	0,3 mm
ro	0.25
DE_	43.262
SRI	2.46
D_a	45
DA_	4.762
SRE	2.46
DI_	33.738
yobi	6906N
mass	0.052
SBRG	19
bomp	0
KBRG	6101
SREX	0.015
SREN	-0.015
SRIN	-0.015

SDM_	38.5
SRIX	0.015
ALPHA_	0
r min.	0,3 mm
C_conv	7250
da max	34 mm
da min	32
Weight	0,052 Kg
LangID	1
ra max.	0,3 mm
Da max.	45 mm
Oil rpm	17000
da min.	32 mm
r0 max.	0,25 mm
hidYobi	6906N
GRS rpm	14000
hidTable	ecat_NSRDGB
Size (mm)	30x47x9
Prod_Type3	DGBB_SR_N_OT
Width (mm)	9
Bearing number	6906N
Bore Diameter (mm)	30
Outer Diameter (mm)	47
(Oil) Lubrication Speed	17 000 r/min
(Grease) Lubrication Speed	14 000 r/min
Basic dynamic load rating (C)	7,25 kN
Basic static load rating (C0)	5 kN