



Bearing No. 6906NR

f	0,85 mm
r	0.3
d	30 mm
D	47 mm
B	9 mm
C	9 mm
a	1,7 mm
b	0,95 mm
D2	49,8 mm
B_	9
Cy	2.3
ra	0.3
C0	5
fo	15.8
D_	47
D1	45,7 mm
rn	0,3 mm
Z_	14
Dx	50.5
ro	0.25
DE_	43.262
DA_	4.762
SRI	2.46
D_a	45
SRE	2.46
DI_	33.738
SRIN	-0.015
yobi	6906NR
SBRG	19
bomp	0

SREX	0.015
KBRG	6101
SREN	-0.015
SDM_	38.5
SRIX	0.015
mass	0.052
C_conv	7250
r min.	0,3 mm
da max	34 mm
ALPHA_	0
Weight	0,052 Kg
da min	32
LangID	1
GRS rpm	14000
Da max.	45 mm
hidYobi	6906NR
Oil rpm	17000
da min.	32 mm
r0 max.	0,25 mm
ra max.	0,3 mm
hidTable	ecat_NSRDGB
Size (mm)	30x47x9
Prod_Type3	DGBB_SR_NR_OT
Width (mm)	9
Bearing number	6906NR
Bore Diameter (mm)	30
Outer Diameter (mm)	47
(Oil) Lubrication Speed	17 000 r/min
(Grease) Lubrication Speed	14 000 r/min
Basic dynamic load rating (C)	7,25 kN
Basic static load rating	5 kN

(C0)	
------	--