



Bearing No. 6902N

a	1,3 mm
r	0.3
d	15 mm
D	28 mm
B	7 mm
C	7 mm
b	0,95 mm
fo	14.3
B_	7
ra	0.3
C0	2.26
D1	26,7 mm
D_	28
Z_	10
rn	0,3 mm
ro	0.25
DE_	25.469
SRI	2.05
D_a	26
DA_	3.969
SRE	2.05
DI_	17.531
yobi	6902N
mass	0.015
SBRG	19
bomp	0
KBRG	6101
SREX	0.015
SREN	-0.015
SRIN	-0.015

SDM_	21.5
SRIX	0.015
ALPHA_	0
r min.	0,3 mm
C_conv	4350
da max	17 mm
da min	17
Weight	0,015 Kg
LangID	1
ra max.	0,3 mm
Da max.	26 mm
Oil rpm	30000
da min.	17 mm
r0 max.	0,25 mm
hidYobi	6902N
GRS rpm	26000
hidTable	ecat_NSRDGB
Size (mm)	15x28x7
Prod_Type3	DGBB_SR_N_OT
Width (mm)	7
Bearing number	6902N
Bore Diameter (mm)	15
Outer Diameter (mm)	28
(Oil) Lubrication Speed	30 000 r/min
(Grease) Lubrication Speed	26 000 r/min
Basic dynamic load rating (C)	4,35 kN
Basic static load rating (C0)	2,26 kN