



Bearing No. 6902NR

f	0,85 mm
r	0.3
d	15 mm
D	28 mm
B	7 mm
C	7 mm
a	1,3 mm
b	0,95 mm
D2	30,8 mm
B_	7
Cy	1.8
ra	0.3
C0	2.26
fo	14.3
D_	28
D1	26,7 mm
rn	0,3 mm
Z_	10
Dx	31.5
ro	0.25
DE_	25.469
DA_	3.969
SRI	2.05
D_a	26
SRE	2.05
DI_	17.531
SRIN	-0.015
yobi	6902NR
SBRG	19
bomp	0

SREX	0.015
KBRG	6101
SREN	-0.015
SDM_	21.5
SRIX	0.015
mass	0.015
C_conv	4350
r min.	0,3 mm
da max	17 mm
ALPHA_	0
Weight	0,015 Kg
da min	17
LangID	1
GRS rpm	26000
Da max.	26 mm
hidYobi	6902NR
Oil rpm	30000
da min.	17 mm
r0 max.	0,25 mm
ra max.	0,3 mm
hidTable	ecat_NSRDGB
Size (mm)	15x28x7
Prod_Type3	DGBB_SR_NR_OT
Width (mm)	7
Bearing number	6902NR
Bore Diameter (mm)	15
Outer Diameter (mm)	28
(Oil) Lubrication Speed	30 000 r/min
(Grease) Lubrication Speed	26 000 r/min
Basic dynamic load rating (C)	4,35 kN
Basic static load rating	2,26 kN

(C0)	
------	--