



### Bearing No. 6902ZENR

a	1.3 mm
f	0.85 mm
b	0.95 mm
d	15 mm
D	28 mm
B	7 mm
C	7 mm
r1	0.3 mm
D2	30.8 mm
D1	26.7 mm
Width	7 mm
Weight	0.017 Kg
r min.	0.3 mm
b (min)	1 mm
r1 min.	0.3 mm
a (max)	1.3 mm
Cy (max)	1.8 mm
D1 (max)	26.7 mm
ra (max)	0.3 mm
Da (max)	26 mm
da (min)	17 mm
Dx (min)	31.5 mm
Factor fo	14.3
Bore Size	15 mm
Size (mm)	15x28x7
Bore Type	Cylindrical Bore
Enclosure	Single Shield with Snap Ring
Width (mm)	7
Configuration	Single Row

Bearing number	6902ZENR
Snap Ring Width	0.9 mm
Outside Diameter	28 mm
Radial Clearance	0.003 to 0.018 mm
Static Load Rating	2,250 N
Bore Diameter (mm)	15
Dynamic Load Rating	4,300 N
Outer Diameter (mm)	28
Limiting Speed - Oil	31,000 rpm
Fillet Radius/Chamfer	0.3 mm
Limiting Speed - Grease	26,000 rpm
Snap Ring Outside Diameter	30.8 mm
(Grease) Lubrication Speed	26000 r/min
Basic static load rating (C0)	2,25 kN
Basic dynamic load rating (C)	4,3 kN