



Bearing No. 6902

C	7 mm
d	15 mm
D	28 mm
B	7 mm
Noun	Bearing
Bore	0.591 Inch 15 Millimeter
Width	7 mm
Weight	0.016 Kg
UNSPSC	31171504
r min.	0.3 mm
Da max.	26 mm
ra max.	0.3 mm
da min.	17 mm
Category	Single Row Ball Bearing
Da (max)	26 mm
da (min)	17 mm
ra (max)	0.3 mm
Bore Size	15 mm
Inventory	0.0
Bore Type	Cylindrical Bore
Factor fo	14.3
Enclosure	Open
Snap Ring	No
Size (mm)	15x28x7
Width (mm)	7
Weight / LBS	0.04
Inch - Metric	Metric
Product Group	B00308
Configuration	Single Row

Keyword String	Ball
Bearing number	6902
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Long Description	15MM Bore; 28MM Outside Diameter; 7MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Radial Clearance	0.003 to 0.018 mm
Outside Diameter	1.102 Inch 28 Millimeter
Manufacturer URL	http://www.nachi.com
Outer Race Width	0.276 Inch 7 Millimeter
Manufacturer Name	NACHI
Weight / Kilogram	0.018
Static Load Rating	2,250 N
Bore Diameter (mm)	15
Internal Clearance	C0-Medium
Outer Diameter (mm)	28
Dynamic Load Rating	4,300 N
Minimum Buy Quantity	N/A
Limiting Speed - Oil	31,000 rpm
Fillet Radius/Chamfer	0.3 mm
Harmonized Tariff Code	8482.10.50.68
Limiting Speed - Grease	26,000 rpm
Manufacturer Item Number	6902 BNLS
Internal Special Features	No
(Grease) Lubrication Speed	26000 r/min
Basic static load rating	2,25 kN

(C0)	
Basic dynamic load rating (C)	4,3 kN
Maximum Capacity / Filling Slot	No