



Bearing No. 6902

D	28 mm
d	15 mm
B	7 mm
C	7 mm
f0	14.3
Cu	0.120
Cr	5.40
C0r	2.25
Bore	0.591 Inch 15 Millimeter
Noun	Bearing
UNSPSC	31171504
Weight	0,017 Kg
r(min)	0.3
r min.	0,3 mm
da min.	17 mm
ra(max)	0.3
Da max.	26 mm
Da(max)	26
da(min)	17
ra max.	0,3 mm
Category	Single Row Ball Bearing
Oil lub.	30000
Inventory	0.0
Enclosure	Open
Size (mm)	15x28x7
Snap Ring	No
Width (mm)	7
Grease lub.	26000
Bearing No.	6902

Weight / LBS	0.036
Product Group	B00308
Cage Material	Steel
Inch - Metric	Metric
Keyword String	Ball
Bearing number	6902
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Long Description	15MM Bore; 28MM Outside Diameter; 7MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Outer Race Width	0.276 Inch 7 Millimeter
Outside Diameter	1.102 Inch 28 Millimeter
(Refer.)Mass(kg)	0.017
Manufacturer URL	http://www.koyousa.com
Weight / Kilogram	0.016
Manufacturer Name	KOYO
Internal Clearance	C0-Medium
Bore Diameter (mm)	15
Outer Diameter (mm)	28
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
(Oil) Lubrication Speed	30000 r/min
Manufacturer Item Number	6902
Internal Special Features	No
(Grease) Lubrication Speed	26000 r/min
Basic static load rating	2,25 kN

(C0)	
Basic dynamic load rating (C)	4,3 kN
Maximum Capacity / Filling Slot	No