



Bearing No. 6902

D	28 mm
d	15 mm
B	7 mm
C	7 mm
r	0.3
Z_	10
C0	2.26
ra	0.3
fo	14.3
D_	28
B_	7
DI_	17.531
SRI	2.05
DE_	25.469
DA_	3.969
SRE	2.05
D_a	26
KBRG	6101
SRIX	0.015
Noun	Bearing
yobi	6902
SDM_	21.5
bomp	0
SRIN	-0.015
mass	0.015
SREX	0.015
Bore	0.591 Inch 15 Millimeter
SBRG	19
SREN	-0.015

ALPHA_	0
UNSPSC	31171504
da max	17 mm
LangID	1
r min.	0,3 mm
C_conv	4350
Weight	0,015 Kg
da min	17
GRS rpm	26000
Oil rpm	30000
hidYobi	6902
da min.	17 mm
Da max.	26 mm
ra max.	0,3 mm
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Inventory	0.0
Snap Ring	No
Size (mm)	15x28x7
Enclosure	Open
bore type:	Round
Prod_Type3	DGBB_SR_OT
Width (mm)	7
Weight / LBS	0.016
maximum rpm:	30000 rpm
Product Group	B00308
closure type:	Open
Cage Material	Steel
Inch - Metric	Metric
Bearing number	6902
bore diameter:	15 mm
cage material:	Steel Cage

overall width:	7 mm
Keyword String	Ball
finish/coating:	Uncoated
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outer Race Width	0.276 Inch 7 Millimeter
Manufacturer URL	http://www.nskamericas.com
Long Description	15MM Bore; 28MM Outside Diameter; 7MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Outside Diameter	1.102 Inch 28 Millimeter
Weight / Kilogram	0.01
Manufacturer Name	NSK
precision rating:	ABEC1, P0
outside diameter:	28 mm
Internal Clearance	C0-Medium
Bore Diameter (mm)	15
snap ring included:	Without Snap Ring
Outer Diameter (mm)	28
internal clearance:	C0
Minimum Buy Quantity	N/A
row type & fill slot:	Single Row Non-Fill Slot
dynamic load capacity:	4350 N
Harmonized Tariff Code	8482.10.50.68
(Oil) Lubrication Speed	30 000 r/min
Manufacturer Item Number	6902
Internal Special Features	No

(Grease) Lubrication Speed	26 000 r/min
Basic static load rating (C ₀)	2,26 kN
Basic dynamic load rating (C)	4,35 kN
Maximum Capacity / Filling Slot	No