



Bearing No. 6901N

| | |
|------|---------|
| a | 1,05 mm |
| r | 0.3 |
| d | 12 mm |
| D | 24 mm |
| B | 6 mm |
| C | 6 mm |
| b | 0,8 mm |
| fo | 14.5 |
| B_ | 6 |
| ra | 0.3 |
| C0 | 1.46 |
| D1 | 22,8 mm |
| D_ | 24 |
| Z_ | 10 |
| rn | 0,2 mm |
| ro | 0.2 |
| DE_ | 21.175 |
| SRI | 1.64 |
| D_a | 22 |
| DA_ | 3.175 |
| SRE | 1.64 |
| DI_ | 14.825 |
| yobi | 6901N |
| mass | 0.01 |
| SBRG | 19 |
| bomp | 0 |
| KBRG | 6101 |
| SREX | 0.015 |
| SREN | -0.015 |
| SRIN | -0.015 |

| | |
|-------------------------------|--------------|
| SDM_ | 18 |
| SRIX | 0.015 |
| ALPHA_ | 0 |
| r min. | 0,3 mm |
| C_conv | 2890 |
| da max | 14,5 mm |
| da min | 14 |
| Weight | 0,01 Kg |
| LangID | 1 |
| ra max. | 0,3 mm |
| Da max. | 22 mm |
| Oil rpm | 36000 |
| da min. | 14 mm |
| r0 max. | 0,2 mm |
| hidYobi | 6901N |
| GRS rpm | 30000 |
| hidTable | ecat_NSRDGB |
| Size (mm) | 12x24x6 |
| Prod_Type3 | DGBB_SR_N_OT |
| Width (mm) | 6 |
| Bearing number | 6901N |
| Bore Diameter (mm) | 12 |
| Outer Diameter (mm) | 24 |
| (Oil) Lubrication Speed | 36 000 r/min |
| (Grease) Lubrication Speed | 30 000 r/min |
| Basic dynamic load rating (C) | 2,89 kN |
| Basic static load rating (C0) | 1,46 kN |