



### Bearing No. 6901VV

D	24 mm
d	12 mm
B	6 mm
C	6 mm
r	0.3
C0	1.46
fo	14.5
ra	0.3
D_	24
B_	6
Z_	10
DI_	14.825
D_a	22
DE_	21.175
SRI	1.64
DA_	3.175
SRE	1.64
Noun	Bearing
SREN	-0.015
SDM_	18
SRIN	-0.015
yobi	6901VV
Bore	0.472 Inch   12 Millimeter
mass	0.01
bomp	0
SREX	0.015
SBRG	19
SRIX	0.015
KBRG	6151

UNSPSC	31171504
ALPHA_	0
LangID	1
r min.	0,3 mm
da max	14,5 mm
da min	14
Weight	0,01 Kg
C_conv	2890
GRS rpm	30000
hidYobi	6901VV
da min.	14 mm
Da max.	22 mm
ra max.	0,3 mm
hidTable	ecat_NSRDGB
Category	Single Row Ball Bearing
Inventory	0.0
Snap Ring	No
Size (mm)	12x24x6
Enclosure	2 Seals
Prod_Type3	DGBB_SR_VV
bore type:	Round
Width (mm)	6
Weight / LBS	0.011
Cage Material	Steel
Product Group	B00308
closure type:	Two Non-Contact Seals
Inch - Metric	Metric
Bearing number	6901VV
bore diameter:	12 mm
overall width:	6 mm
Keyword String	Ball
Enclosure Type	Non-Contact Seal

Rolling Element	Ball Bearing
Precision Class	ABEC 1   ISO P0
Outside Diameter	0.945 Inch   24 Millimeter
Long Description	12MM Bore; 24MM Outside Diameter; 6MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Outer Race Width	0.236 Inch   6 Millimeter
Manufacturer URL	<a href="http://www.nskamericas.com">http://www.nskamericas.com</a>
Weight / Kilogram	0.01
bearing material:	Steel
outside diameter:	24 mm
Manufacturer Name	NSK
maximum rpm (oil):	36000 rpm
Bore Diameter (mm)	12
Internal Clearance	C0-Medium
Outer Diameter (mm)	24
snap ring included:	Without Snap Ring
internal clearance:	C0
Minimum Buy Quantity	N/A
maximum rpm (grease):	30000 rpm
static load capacity:	330 lbs
row type & fill slot:	Single Row Non-Fill Slot
manufacturer catalog:	<a href="#">Click here</a>
dynamic load capacity:	650 lbs
Harmonized Tariff Code	8482.10.50.68
manufacturer upc number:	029176030536
Manufacturer Item Number	6901VV

Internal Special Features	No
(Grease) Lubrication Speed	30 000 r/min
Basic static load rating (C0)	1,46 kN
Basic dynamic load rating (C)	2,89 kN
Maximum Capacity / Filling Slot	No