



Bearing No. 6900ZZE

D	22 mm
d	10 mm
B	6 mm
C	6 mm
Noun	Bearing
Bore	0.394 Inch 10 Millimeter
Width	6 mm
UNSPSC	31171504
r min.	0.3 mm
Weight	0.009 Kg
da min.	12 mm
Da max.	20 mm
ra max.	0.3 mm
Category	Single Row Ball Bearing
ra (max)	0.3 mm
Da (max)	20 mm
da (min)	12 mm
Factor fo	14.0
Inventory	0.0
Bore Size	10 mm
Bore Type	Cylindrical Bore
Enclosure	2 Metal Shields
Snap Ring	No
Size (mm)	10x22x6
Width (mm)	6
Configuration	Single Row
Product Group	B00308
Cage Material	Steel
Inch - Metric	Metric

Other Features	Deep Groove
Keyword String	Ball
Bearing number	6900ZZE
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Long Description	10MM Bore; 22MM Outside Diameter; 6MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel
Manufacturer URL	http://www.nachiamerica.com
Outer Race Width	0.236 Inch 6 Millimeter
Outside Diameter	0.866 Inch 22 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Radial Clearance	0.002 to 0.013 mm
Weight / Kilogram	0.009
Manufacturer Name	NACHI
Bore Diameter (mm)	10
Internal Clearance	C0-Medium
Static Load Rating	1,130 N
Dynamic Load Rating	2,490 N
Outer Diameter (mm)	22
Minimum Buy Quantity	N/A
Fillet Radius/Chamfer	0.3 mm
Harmonized Tariff Code	8482.10.50.68
Limiting Speed - Grease	33,000 rpm
Internal Special Features	No
Basic dynamic load	2,49 kN

rating (C)	
Basic static load rating (C0)	1,13 kN
Maximum Capacity / Filling Slot	No