



Bearing No. 6900NR

| | |
|------|---------|
| f | 0,7 mm |
| r | 0.3 |
| d | 10 mm |
| D | 22 mm |
| B | 6 mm |
| C | 6 mm |
| a | 1,05 mm |
| b | 0,8 mm |
| D2 | 24,8 mm |
| B_ | 6 |
| Cy | 1.5 |
| ra | 0.3 |
| C0 | 1.27 |
| fo | 14 |
| D_ | 22 |
| D1 | 20,8 mm |
| rn | 0,2 mm |
| Z_ | 9 |
| Dx | 25.5 |
| ro | 0.2 |
| DE_ | 19.175 |
| DA_ | 3.175 |
| SRI | 1.64 |
| D_a | 20 |
| SRE | 1.64 |
| DI_ | 12.825 |
| SRIN | -0.015 |
| yobi | 6900NR |
| SBRG | 19 |
| bomp | 0 |

| | |
|-------------------------------|---------------|
| SREX | 0.015 |
| KBRG | 6101 |
| SREN | -0.015 |
| SDM_ | 16 |
| SRIX | 0.015 |
| mass | 0.009 |
| C_conv | 2700 |
| r min. | 0,3 mm |
| da max | 12,5 mm |
| ALPHA_ | 0 |
| Weight | 0,009 Kg |
| da min | 12 |
| LangID | 1 |
| GRS rpm | 32000 |
| Da max. | 20 mm |
| hidYobi | 6900NR |
| Oil rpm | 38000 |
| da min. | 12 mm |
| r0 max. | 0,2 mm |
| ra max. | 0,3 mm |
| hidTable | ecat_NSRDGB |
| Size (mm) | 10x22x6 |
| Prod_Type3 | DGBB_SR_NR_OT |
| Width (mm) | 6 |
| Bearing number | 6900NR |
| Bore Diameter (mm) | 10 |
| Outer Diameter (mm) | 22 |
| (Oil) Lubrication Speed | 38 000 r/min |
| (Grease) Lubrication Speed | 32 000 r/min |
| Basic dynamic load rating (C) | 2,7 kN |
| Basic static load rating | 1,27 kN |

| | |
|------|--|
| (C0) | |
|------|--|