



Bearing No. 6900VV

D	22 mm
d	10 mm
B	6 mm
C	6 mm
r	0.3
Z_	9
B_	6
D_	22
ra	0.3
C0	1.27
fo	14
DI_	12.825
SRI	1.64
D_a	20
DE_	19.175
DA_	3.175
SRE	1.64
SRIN	-0.015
SBRG	19
yobi	6900VV
SDM_	16
SREX	0.015
KBRG	6151
bomp	0
mass	0.009
Bore	0.394 Inch 10 Millimeter
SRIX	0.015
SREN	-0.015
Noun	Bearing

ALPHA_	0
da min	12
LangID	1
r min.	0,3 mm
UNSPSC	31171504
C_conv	2700
da max	12,5 mm
Weight	0,009 Kg
hidYobi	6900VV
Da max.	20 mm
da min.	12 mm
ra max.	0,3 mm
GRS rpm	32000
hidTable	ecat_NSRDGB
Category	Single Row Ball Bearing
Inventory	5.0
Enclosure	2 Seals
Snap Ring	No
Size (mm)	10x22x6
Width (mm)	6
Prod_Type3	DGBB_SR_VV
Weight / LBS	0.009
Product Group	B00308
Cage Material	Steel
Inch - Metric	Metric
Bearing number	6900VV
Keyword String	Ball
Enclosure Type	Non-Contact Seal
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outside Diameter	0.866 Inch 22 Millimeter
Outer Race Width	0.236 Inch 6 Millimeter

Long Description	10MM Bore; 22MM Outside Diameter; 6MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer URL	http://www.nskamericas.com
Weight / Kilogram	0.01
Manufacturer Name	NSK
Internal Clearance	C0-Medium
Bore Diameter (mm)	10
Outer Diameter (mm)	22
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6900VV
Internal Special Features	No
(Grease) Lubrication Speed	32 000 r/min
Basic static load rating (C0)	1,27 kN
Basic dynamic load rating (C)	2,7 kN
Maximum Capacity / Filling Slot	No