



### Bearing No. 6319VV

r	3
d	95 mm
D	200 mm
B	45 mm
C	45 mm
fo	13.3
D_	200
B_	45
ra	2.5
Z_	8
C0	119
DI_	114.162
SRE	17.25
D_a	187
DE_	180.838
SRI	17.25
DA_	33.338
SREN	-0.065
Bore	3.74 Inch   95 Millimeter
SRIN	-0.065
bomp	0
SRIX	0.065
yobi	6319VV
mass	5.76
SDM_	147.5
KBRG	6151
SREX	0.065
SBRG	3
Noun	Bearing
da max	123,5 mm

Weight	5,76 Kg
LangID	1
r min.	3 mm
da min	108
ALPHA_	0
C_conv	153000
UNSPSC	31171504
da min.	108 mm
hidYobi	6319VV
GRS rpm	3000
Da max.	187 mm
ra max.	2,5 mm
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Snap Ring	No
Enclosure	2 Seals
Size (mm)	95x200x45
Inventory	0.0
Prod_Type3	DGBB_SR_VV
Width (mm)	45
Weight / LBS	12.7008
Product Group	B00308
Inch - Metric	Metric
Cage Material	Steel
Bearing number	6319VV
Enclosure Type	Non-Contact Seal
Other Features	Deep Groove   Rubber Seal
Keyword String	Ball
Rolling Element	Ball Bearing
Precision Class	ABEC 1   ISO P0
Inner Race Width	0 Inch   0 Millimeter
Outer Race Width	1.772 Inch   45

	Millimeter
Long Description	95MM Bore; 200MM Outside Diameter; 45MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage;
Manufacturer URL	<a href="http://www.nskamericas.com">http://www.nskamericas.com</a>
Outside Diameter	7.874 Inch   200 Millimeter
Weight / Kilogram	5.76
Manufacturer Name	NSK
Internal Clearance	C0-Medium
Bore Diameter (mm)	95
Outer Diameter (mm)	200
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Internal Special Features	No
(Grease) Lubrication Speed	3 000 r/min
Basic dynamic load rating (C)	153 kN
Basic static load rating (C0)	119 kN
Maximum Capacity / Filling Slot	No