



Bearing No. 6319ZZ

D	200 mm
d	95 mm
B	45 mm
C	45 mm
r	3
ra	2.5
Z_	8
B_	45
D_	200
fo	13.3
C0	119
D_a	187
DE_	180.838
DI_	114.162
SRE	17.25
SRI	17.25
DA_	33.338
SRIX	0.065
bomp	0
SRIN	-0.065
Noun	Bearing
Bore	3.74 Inch 95 Millimeter
SREN	-0.065
SREX	0.065
mass	5.76
KBRG	6141
SBRG	3
yobi	6319ZZ
SDM_	147.5
Weight	5,76 Kg

LangID	1
r min.	3 mm
ALPHA_	0
UNSPSC	31171504
da min	108
C_conv	153000
da max	123,5 mm
da min.	108 mm
GRS rpm	3000
hidYobi	6319ZZ
ra max.	2,5 mm
Da max.	187 mm
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Enclosure	2 Metal Shields
Size (mm)	95x200x45
Inventory	0.0
Snap Ring	No
Width (mm)	45
Prod_Type3	DGBB_SR_ZZ
Weight / LBS	5.85
Product Group	B00308
Inch - Metric	Metric
Cage Material	Steel
Bearing number	6319ZZ
Keyword String	Ball
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Manufacturer URL	http://www.nskamericas.com
Outside Diameter	7.874 Inch 200 Millimeter
Outer Race Width	1.772 Inch 45

	Millimeter
Long Description	95MM Bore; 200MM Outside Diameter; 45MM Outer Race Diameter; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer Name	NSK
Weight / Kilogram	5.9
Internal Clearance	C0-Medium
Bore Diameter (mm)	95
Outer Diameter (mm)	200
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6319ZZ
Internal Special Features	No
(Grease) Lubrication Speed	3 000 r/min
Basic static load rating (C0)	119 kN
Basic dynamic load rating (C)	153 kN
Maximum Capacity / Filling Slot	No