



Bearing No. 69/530

| | |
|--------|--------|
| r | 5 |
| d | 530 mm |
| D | 710 mm |
| B | 82 mm |
| C | 82 mm |
| C0 | 870 |
| Z_ | 20 |
| ra | 4 |
| B_ | 82 |
| D_ | 710 |
| fo | 16.8 |
| D_a | 690 |
| SRE | 26.29 |
| DE_ | 670.8 |
| DA_ | 50.8 |
| DI_ | 569.2 |
| SRI | 26.29 |
| mass | 89.8 |
| SRIN | -0.1 |
| SBRG | 19 |
| SRIX | 0.1 |
| KBRG | 6104 |
| SREN | -0.1 |
| yobi | 69/530 |
| bomp | 0 |
| SREX | 0.1 |
| SDM_ | 620 |
| r min. | 5 mm |
| ALPHA_ | 0 |
| da min | 550 |
| | |

| | |
|-------------------------------|-------------|
| C_conv | 455000 |
| Weight | 89,8 Kg |
| LangID | 1 |
| Oil rpm | 800 |
| GRS rpm | 670 |
| hidYobi | 69/530 |
| ra max. | 4 mm |
| Da max. | 676 mm |
| da min. | 572 mm |
| hidTable | ecat_NSRDGB |
| Size (mm) | 530x710x82 |
| Prod_Type3 | DGBB_SR_OT |
| Width (mm) | 82 |
| Bearing number | 69/530 |
| Bore Diameter (mm) | 530 |
| Outer Diameter (mm) | 710 |
| Basic static load rating (C0) | 870 kN |
| Basic dynamic load rating (C) | 455 kN |