



Bearing No. 63208LLB

D	80,000 mm
C	30,162 mm
B	30,162 mm
d	40,000 mm
Noun	Bearing
Bore	1.575 Inch 40 Millimeter
UNSPSC	31171504
Category	Single Row Ball Bearing
Snap Ring	No
Inventory	0.0
Enclosure	2 Seals
Size (mm)	40x80x30.162
Width (mm)	30,162
bore type:	Round
Weight / LBS	1.28
closure type:	Double Sealed
Inch - Metric	Metric
Cage Material	Steel
Product Group	B00308
Bearing number	63208LLB
Keyword String	Ball
bore diameter:	40 mm
cage material:	Steel
overall width:	30.2 mm
Other Features	Deep Groove Cartridge Type Non-Friction Nitrile Rubber Seal Shell Alvania Prelubricated
Enclosure Type	Non-Contact Seal
fillet radius:	1.1 mm

Precision Class	ABEC 1 ISO P0
finish/coating:	Uncoated
Rolling Element	Ball Bearing
Outside Diameter	3.15 Inch 80 Millimeter
Outer Race Width	1.188 Inch 30.18 Millimeter
Long Description	40MM Bore; 80MM Outside Diameter; 30.18MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cag
Inner Race Width	0 Inch 0 Millimeter
Manufacturer URL	http://www.ntnamerica.com
outer ring width:	30.20 mm
Weight / Kilogram	0
outside diameter:	80 mm
precision rating:	ISO Class 0
inner ring width:	30.20 mm
Manufacturer Name	NTN
bearing material:	High Carbon Chrome Steel
Bore Diameter (mm)	40,000
Internal Clearance	C0-Medium
snap ring included:	Without Snap Ring
internal clearance:	CN
Outer Diameter (mm)	80,000
Minimum Buy Quantity	N/A
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	8700 rpm
static load capacity:	2390 N

dynamic load capacity:	5100 N
Harmonized Tariff Code	8482.10.50.68
Internal Special Features	No
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Maximum Capacity / Filling Slot	No