



**Bearing No. 63209ZZ**

D	85,000 mm
d	45,000 mm
B	30,162 mm
C	30,162 mm
Noun	Bearing
Bore	1.772 Inch   45 Millimeter
UNSPSC	31171504
series:	632
Category	Single Row Ball Bearing
Snap Ring	No
Enclosure	2 Metal Shields
Size (mm)	45x85x30.162
Inventory	0.0
bore type:	Round
Width (mm)	30,162
Weight / LBS	1.37
closure type:	Double Shielded
Product Group	B00308
Cage Material	Steel
Inch - Metric	Metric
overall width:	30.2 mm
bore diameter:	40 mm
fillet radius:	1.1 mm
Keyword String	Ball
cage material:	Steel
Bearing number	63209ZZ
Other Features	Deep Groove   Cartridge Type   Shell Alvania Prelubricated
finish/coating:	Uncoated

Rolling Element	Ball Bearing
Precision Class	ABEC 1   ISO P0
Long Description	45MM Bore; 85MM Outside Diameter; 30.18MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; S
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Outside Diameter	3.346 Inch   85 Millimeter
Outer Race Width	1.188 Inch   30.18 Millimeter
Inner Race Width	0 Inch   0 Millimeter
outer ring width:	30.20 mm
inner ring width:	30.20 mm
Manufacturer Name	NTN
Weight / Kilogram	0
bearing material:	High Carbon Chrome Steel
outside diameter:	80 mm
precision rating:	ISO Class 0
Internal Clearance	C0-Medium
Bore Diameter (mm)	45,000
Outer Diameter (mm)	85,000
internal clearance:	CN
snap ring included:	Without Snap Ring
Minimum Buy Quantity	N/A
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	7800 rpm
static load capacity:	2390 N

Harmonized Tariff Code	8482.10.50.68
dynamic load capacity:	5100 N
Internal Special Features	No
manufacturer product page:	<a href="#">Click here</a>
operating temperature range:	-40 to 120 °C
Maximum Capacity / Filling Slot	No