



Bearing No. 6320DDU

r	3
d	100 mm
D	215 mm
B	47 mm
C	47 mm
D_	215
C0	141
Z_	8
ra	2.5
fo	13.2
B_	47
DI_	122.488
SRI	18.89
SRE	18.89
DE_	195.512
DA_	36.512
D_a	202
KBRG	6161
SBRG	3
SRIN	-0.065
bomp	0
SREX	0.065
yobi	6320DDU
SRIX	0.065
Bore	3.937 Inch   100 Millimeter
SDM_	159
SREN	-0.065
mass	7.04
Noun	Bearing

LangID	1
UNSPSC	31171504
da min	113
r min.	3 mm
Weight	7,04 Kg
ALPHA_	0
C_conv	173000
da max	133 mm
GRS rpm	2200
Da max.	202 mm
ra max.	2,5 mm
da min.	113 mm
hidYobi	6320DDU
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Size (mm)	100x215x47
Enclosure	2 Seals
Snap Ring	No
Inventory	0.0
Width (mm)	47
Prod_Type3	DGBB_SR_DD
Weight / LBS	15.5232
Inch - Metric	Metric
Product Group	B00308
Cage Material	Steel
Bearing number	6320DDU
Keyword String	Ball
Other Features	Deep Groove   Rubber Seal
Enclosure Type	Contact Seal
Precision Class	ABEC 1   ISO P0
Rolling Element	Ball Bearing
Outer Race Width	1.85 Inch   47 Millimeter

Inner Race Width	0 Inch   0 Millimeter
Long Description	100MM Bore; 215MM Outside Diameter; 47MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage
Manufacturer URL	<a href="http://www.nskamericas.com">http://www.nskamericas.com</a>
Outside Diameter	8.465 Inch   215 Millimeter
Manufacturer Name	NSK
Weight / Kilogram	7
Internal Clearance	C0-Medium
Bore Diameter (mm)	100
Outer Diameter (mm)	215
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6320DDU
Internal Special Features	No
(Grease) Lubrication Speed	2 200 r/min
Basic static load rating (C0)	141 kN
Basic dynamic load rating (C)	173 kN
Maximum Capacity / Filling Slot	No