



### Bearing No. 6320LLU

D	215 mm
d	100 mm
B	47 mm
C	47 mm
Bore	3.937 Inch   100 Millimeter
Noun	Bearing
da max	133 mm
UNSPSC	31171504
r min.	3 mm
Weight	7 Kg
ra max.	2,5 mm
da min.	113 mm
Da max.	202 mm
Category	Single Row Ball Bearing
Snap Ring	No
Size (mm)	100x215x47
Enclosure	2 Seals
Inventory	0.0
Width (mm)	47
Weight / LBS	15.4
Product Group	B00308
Inch - Metric	Metric
Cage Material	Steel
Enclosure Type	Contact Seal
Other Features	Deep Groove   Double Lip Friction Nitrile Rubber Seal   -20 To 120 Deg C   Shell Alvania Prelubricated
Keyword String	Ball
Bearing number	6320LLU

Rolling Element	Ball Bearing
Precision Class	ABEC 1   ISO P0
Reference speed	2 200 r/min
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Long Description	100MM Bore; 215MM Outside Diameter; 47MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage
Inner Race Width	0 Inch   0 Millimeter
Outer Race Width	1.85 Inch   47 Millimeter
Outside Diameter	8.465 Inch   215 Millimeter
Weight / Kilogram	7.19
Manufacturer Name	NTN
Internal Clearance	C0-Medium
Bore Diameter (mm)	100
Outer Diameter (mm)	215
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Internal Special Features	No
Basic static load rating (C0)	141 kN
Basic dynamic load rating (C)	173 kN
Maximum Capacity / Filling Slot	No