



Bearing No. 63206LLU

C	23,800 mm
d	30,000 mm
B	23,800 mm
D	62,000 mm
Bore	1.181 Inch 30 Millimeter
Noun	Bearing
UNSPSC	31171504
series:	632
Category	Single Row Ball Bearing
Size (mm)	30x62x23.800
Inventory	0.0
Enclosure	2 Seals
Snap Ring	No
Width (mm)	23,800
bore type:	Round
Weight / LBS	0.63
Cage Material	Steel
Inch - Metric	Metric
Product Group	B00308
closure type:	Double Sealed
bore diameter:	30 mm
overall width:	23.8 mm
Keyword String	Ball
fillet radius:	1 mm
cage material:	Steel
Bearing number	63206LLU
Other Features	Deep Groove Cartridge Type Double Lip Friction Nitrile Rubber Seal -20 To 120 Deg C Shell Alvania

	Prelubricated
Enclosure Type	Contact Seal
finish/coating:	Uncoated
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Manufacturer URL	http://www.ntnamerica.com
Inner Race Width	0 Inch 0 Millimeter
Outside Diameter	2.441 Inch 62 Millimeter
Outer Race Width	0.938 Inch 23.825 Millimeter
Long Description	30MM Bore; 62MM Outside Diameter; 23.825MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Ca
outer ring width:	23.80 mm
inner ring width:	23.80 mm
Manufacturer Name	NTN
Weight / Kilogram	0
bearing material:	High Carbon Chrome Steel
outside diameter:	62 mm
precision rating:	ISO Class 0
Bore Diameter (mm)	30,000
Internal Clearance	C0-Medium
Outer Diameter (mm)	62,000
internal clearance:	CN
snap ring included:	Without Snap Ring
Minimum Buy Quantity	N/A

row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	7300 rpm
static load capacity:	2390 N
Harmonized Tariff Code	8482.10.50.68
dynamic load capacity:	5100 N
Internal Special Features	No
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Maximum Capacity / Filling Slot	No