



**Bearing No. 63210LLB**

D	90,000 mm
d	50,000 mm
B	30,162 mm
C	30,162 mm
Noun	Bearing
Bore	1.969 Inch   50 Millimeter
UNSPSC	31171504
Category	Single Row Ball Bearing
Enclosure	2 Seals
Size (mm)	50x90x30.162
Snap Ring	No
Inventory	0.0
bore type:	Round
Width (mm)	30,162
Weight / LBS	1.45
Product Group	B00308
closure type:	Double Sealed
Cage Material	Steel
Inch - Metric	Metric
overall width:	30.2 mm
Other Features	Deep Groove   Cartridge Type   Non-Friction Nitrile Rubber Seal
bore diameter:	50 mm
Keyword String	Ball
cage material:	Steel
fillet radius:	1.1 mm
Bearing number	63210LLB
Enclosure Type	Non-Contact Seal
Rolling Element	Ball Bearing

Precision Class	ABEC 1   ISO P0
finish/coating:	Uncoated
Long Description	50MM Bore; 90MM Outside Diameter; 30.18MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cag
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Outside Diameter	3.543 Inch   90 Millimeter
Inner Race Width	0 Inch   0 Millimeter
Outer Race Width	1.188 Inch   30.18 Millimeter
precision rating:	ISO Class 0
outer ring width:	30.20 mm
inner ring width:	30.20 mm
Manufacturer Name	NTN
bearing material:	High Carbon Chrome Steel
Weight / Kilogram	0.684
outside diameter:	90 mm
Bore Diameter (mm)	50,000
Internal Clearance	C0-Medium
Outer Diameter (mm)	90,000
snap ring included:	Without Snap Ring
internal clearance:	CN
Minimum Buy Quantity	N/A
static load capacity:	2390 N
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	3000 rpm

dynamic load capacity:	5100 N
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	63210LLB
Internal Special Features	No
manufacturer product page:	<a href="#">Click here</a>
operating temperature range:	-40 to 120 °C
Maximum Capacity / Filling Slot	No