



Bearing No. 63210LLU

D	90,000 mm
C	30,162 mm
B	30,162 mm
d	50,000 mm
Noun	Bearing
Bore	1.969 Inch 50 Millimeter
UNSPSC	31171504
Category	Single Row Ball Bearing
Snap Ring	No
Inventory	0.0
Enclosure	2 Seals
Size (mm)	50x90x30.162
Width (mm)	30,162
bore type:	Round
Weight / LBS	1.45
closure type:	Double Sealed
Inch - Metric	Metric
Cage Material	Steel
Product Group	B00308
Bearing number	63210LLU
Keyword String	Ball
bore diameter:	50 mm
cage material:	Steel
overall width:	30.2 mm
Other Features	Deep Groove Cartridge Type Double Lip Friction Nitrile Rubber Seal -20 To 120 Deg C Shell Alvania Prelubricated
Enclosure Type	Contact Seal

fillet radius:	1.1 mm
finish/coating:	Uncoated
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Long Description	50MM Bore; 90MM Outside Diameter; 30.18MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cag
Outer Race Width	1.188 Inch 30.18 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Outside Diameter	3.543 Inch 90 Millimeter
Manufacturer URL	http://www.ntnamerica.com
outer ring width:	30.20 mm
Weight / Kilogram	0
outside diameter:	90 mm
precision rating:	ISO Class 0
inner ring width:	30.20 mm
Manufacturer Name	NTN
bearing material:	High Carbon Chrome Steel
Bore Diameter (mm)	50,000
Internal Clearance	C0-Medium
snap ring included:	Without Snap Ring
internal clearance:	CN
Outer Diameter (mm)	90,000
Minimum Buy Quantity	N/A
row type & fill slot:	Single Row Non-Fill Slot

maximum rpm (grease):	2100 rpm
static load capacity:	2390 N
dynamic load capacity:	5100 N
Harmonized Tariff Code	8482.10.50.68
Internal Special Features	No
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Maximum Capacity / Filling Slot	No