



Bearing No. 6322ZZ

C	50 mm
d	110 mm
D	240 mm
B	50 mm
Bore	4.331 Inch 110 Millimeter
Noun	Bearing
Weight	9,54 Kg
r min.	3 mm
da max	149 mm
UNSPSC	31171504
da min.	123 mm
Da max.	227 mm
ra max.	2,5 mm
Category	Single Row Ball Bearing
Size (mm)	110x240x50
Snap Ring	No
Inventory	0.0
Enclosure	2 Metal Shields
Width (mm)	50
bore type:	Round
Weight / LBS	21.032
Inch - Metric	Metric
closure type:	Double Shielded
Product Group	B00308
Cage Material	Steel
bore diameter:	110 mm
Keyword String	Ball
overall width:	50 mm
cage material:	Steel

fillet radius:	3 mm
Other Features	Deep Groove Shell Alvania Prelubricated
Bearing number	6322ZZ
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
finish/coating:	Uncoated
Long Description	110MM Bore; 240MM Outside Diameter; 50MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; St
Manufacturer URL	http://www.ntnamerica.com
Outside Diameter	9.449 Inch 240 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	1.969 Inch 50 Millimeter
precision rating:	ISO Class 0
outer ring width:	50 mm
inner ring width:	50 mm
Weight / Kilogram	0
bearing material:	High Carbon Chrome Steel
Manufacturer Name	NTN
outside diameter:	240 mm
Bore Diameter (mm)	110
Internal Clearance	C0-Medium
snap ring included:	Without Snap Ring
Outer Diameter (mm)	240

internal clearance:	CN
Minimum Buy Quantity	N/A
static load capacity:	179000 N
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	2900 rpm
Harmonized Tariff Code	8482.10.50.68
dynamic load capacity:	205000 N
Internal Special Features	No
(Grease) Lubrication Speed	2 900 r/min
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Basic static load rating (C0)	179 kN
Basic dynamic load rating (C)	205 kN
Maximum Capacity / Filling Slot	No