



Bearing No. 6322ZZ

D	240 mm
d	110 mm
B	50 mm
C	50 mm
Noun	Bearing
Bore	4.331 Inch 110 Millimeter
Width	50 mm
UNSPSC	31171504
r min.	3 mm
Weight	9.54 Kg
da min.	124 mm
Da max.	226 mm
ra max.	2.5 mm
Category	Single Row Ball Bearing
ra (max)	2.5 mm
Da (max)	226 mm
da (min)	124 mm
Factor fo	13.1
Inventory	0.0
Bore Size	110 mm
Bore Type	Cylindrical Bore
Enclosure	2 Metal Shields
Snap Ring	No
Size (mm)	110x240x50
Width (mm)	50
Configuration	Single Row
Product Group	B00308
Cage Material	Steel
Inch - Metric	Metric

Other Features	Deep Groove
Keyword String	Ball
Bearing number	6322ZZ
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Long Description	110MM Bore; 240MM Outside Diameter; 50MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; St
Manufacturer URL	http://www.nachiamerica.com
Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	1.969 Inch 50 Millimeter
Outside Diameter	9.449 Inch 240 Millimeter
Radial Clearance	0.015 to 0.041 mm
Weight / Kilogram	0
Manufacturer Name	NACHI
Bore Diameter (mm)	110
Internal Clearance	C0-Medium
Static Load Rating	179,000 N
Dynamic Load Rating	205,000 N
Outer Diameter (mm)	240
Minimum Buy Quantity	N/A
Fillet Radius/Chamfer	3 mm
Harmonized Tariff Code	8482.10.50.68
Limiting Speed - Grease	2,900 rpm
Internal Special Features	No

Basic dynamic load rating (C)	205 kN
Basic static load rating (C0)	179 kN
Maximum Capacity / Filling Slot	No