



Bearing No. 6322ZZ

r	3
d	110 mm
D	240 mm
B	50 mm
C	50 mm
Z_	8
B_	50
D_	240
fo	13.2
ra	2.5
C0	179
DI_	135.725
DE_	218.275
DA_	41.275
D_a	227
SRI	21.36
SRE	21.36
Bore	4.331 Inch 110 Millimeter
SRIN	-0.08
Noun	Bearing
bomp	0
SREN	-0.08
SREX	0.08
SRIX	0.08
mass	9.51
KBRG	6141
SBRG	3
yobi	6322ZZ
SDM_	177

Weight	9,51 Kg
LangID	1
r min.	3 mm
ALPHA_	0
UNSPSC	31171504
da min	123
C_conv	205000
da max	147 mm
da min.	123 mm
GRS rpm	2400
hidYobi	6322ZZ
ra max.	2,5 mm
Da max.	227 mm
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Enclosure	2 Metal Shields
Size (mm)	110x240x50
Inventory	0.0
Snap Ring	No
Width (mm)	50
Prod_Type3	DGBB_SR_ZZ
Weight / LBS	21
Product Group	B00308
Inch - Metric	Metric
Cage Material	Steel
Bearing number	6322ZZ
Keyword String	Ball
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Manufacturer URL	http://www.nskamericas.com
Outer Race Width	1.969 Inch 50 Millimeter

Outside Diameter	9.449 Inch 240 Millimeter
Long Description	110MM Bore; 240MM Outside Diameter; 50MM Outer Race Diameter; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer Name	NSK
Weight / Kilogram	9.53
Internal Clearance	C0-Medium
Bore Diameter (mm)	110
Outer Diameter (mm)	240
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6322ZZ
Internal Special Features	No
(Grease) Lubrication Speed	2 400 r/min
Basic static load rating (C0)	179 kN
Basic dynamic load rating (C)	205 kN
Maximum Capacity / Filling Slot	No