



Bearing No. 6324ZZS

| | |
|--------|---------|
| r | 3 |
| d | 120 mm |
| D | 260 mm |
| B | 55 mm |
| C | 55 mm |
| fo | 13.5 |
| ra | 2.5 |
| D_ | 260 |
| C0 | 185 |
| B_ | 55 |
| Z_ | 8 |
| SRI | 21.36 |
| DE_ | 231.275 |
| DA_ | 41.275 |
| DI_ | 148.725 |
| SRE | 21.36 |
| D_a | 247 |
| SREX | 0.08 |
| mass | 12.5 |
| SRIN | -0.08 |
| bomp | 0 |
| SREN | -0.08 |
| yobi | 6324ZZS |
| SDM_ | 190 |
| KBRG | 6141 |
| SBRG | 3 |
| SRIX | 0.08 |
| C_conv | 207000 |
| ALPHA_ | 0 |
| da min | 133 |
| | |

| | |
|-------------------------------|-------------|
| Weight | 12,5 Kg |
| r min. | 3 mm |
| LangID | 1 |
| da max | 161 mm |
| ra max. | 2,5 mm |
| da min. | 133 mm |
| Da max. | 247 mm |
| GRS rpm | 2200 |
| hidYobi | 6324ZZS |
| hidTable | ecat_NSRDGB |
| Size (mm) | 120x260x55 |
| Prod_Type3 | DGBB_SR_ZZ |
| Width (mm) | 55 |
| Bearing number | 6324ZZS |
| Bore Diameter (mm) | 120 |
| Outer Diameter (mm) | 260 |
| (Grease) Lubrication Speed | 2 200 r/min |
| Basic dynamic load rating (C) | 207 kN |
| Basic static load rating (C0) | 185 kN |