



Bearing No. 6832DDU

r	1.1
d	160 mm
D	200 mm
B	20 mm
C	20 mm
D_	200
C0	61
Z_	25
ra	1
fo	17.2
B_	20
DI_	168.094
SRI	6.16
SRE	6.16
DE_	191.906
DA_	11.906
D_a	193.5
KBRG	6161
SBRG	18
SRIN	-0.025
bomp	0
SREX	0.025
yobi	6832DDU
SRIX	0.025
mass	1.23
SDM_	180
SREN	-0.025
Bore	6.299 Inch 160 Millimeter
Noun	Bearing

LangID	1
UNSPSC	31171504
da min	166.5
r min.	1,1 mm
Weight	1,23 Kg
ALPHA_	0
C_conv	48500
da max	170,5 mm
GRS rpm	1700
Da max.	193,5 mm
ra max.	1 mm
da min.	166,5 mm
hidYobi	6832DDU
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Size (mm)	160x200x20
Enclosure	2 Seals
Snap Ring	No
Inventory	0.0
Width (mm)	20
Prod_Type3	DGBB_SR_DD
Weight / LBS	1.23
Inch - Metric	Metric
Product Group	B00308
Cage Material	Steel
Bearing number	6832DDU
Keyword String	Ball
Other Features	Deep Groove Rubber Seal
Enclosure Type	Contact Seal
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outer Race Width	0.787 Inch 20

	Millimeter
Outside Diameter	7.874 Inch 200 Millimeter
Long Description	160MM Bore; 200MM Outside Diameter; 20MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage
Manufacturer URL	http://www.nskamericas.com
Inner Race Width	0 Inch 0 Millimeter
Manufacturer Name	NSK
Weight / US pound	1.23
Internal Clearance	C0-Medium
Bore Diameter (mm)	160
Outer Diameter (mm)	200
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6832DDU
Internal Special Features	No
(Grease) Lubrication Speed	1 700 r/min
Basic static load rating (C0)	61 kN
Basic dynamic load rating (C)	48,5 kN
Maximum Capacity / Filling Slot	No