



Bearing No. 6832N

a	3,3 mm
r	1.1
d	160 mm
D	200 mm
B	20 mm
C	20 mm
b	1,9 mm
fo	17.2
B_	20
ra	1
C0	61
D1	196,8 mm
D_	200
Z_	25
rn	0,5 mm
ro	0.6
DE_	191.906
SRI	6.16
D_a	193.5
DA_	11.906
SRE	6.16
DI_	168.094
yobi	6832N
mass	1.23
SBRG	18
bomp	0
KBRG	6101
SREX	0.025
SREN	-0.025
SRIN	-0.025

SDM_	180
SRIX	0.025
ALPHA_	0
r min.	1,1 mm
C_conv	48500
da max	170,5 mm
da min	166.5
Weight	1,23 Kg
LangID	1
ra max.	1 mm
Da max.	193,5 mm
Oil rpm	3200
da min.	166,5 mm
r0 max.	0,6 mm
hidYobi	6832N
GRS rpm	2600
hidTable	ecat_NSRDGB
Size (mm)	160x200x20
Prod_Type3	DGBB_SR_N_OT
Width (mm)	20
Bearing number	6832N
Bore Diameter (mm)	160
Outer Diameter (mm)	200
(Oil) Lubrication Speed	3 200 r/min
(Grease) Lubrication Speed	2 600 r/min
Basic dynamic load rating (C)	48,5 kN
Basic static load rating (C0)	61 kN