



Bearing No. 6832NR

f	1,7 mm
r	1.1
d	160 mm
D	200 mm
B	20 mm
C	20 mm
a	3,3 mm
b	1,9 mm
D2	206,5 mm
B_	20
Cy	4.7
ra	1
C0	61
fo	17.2
D_	200
D1	196,8 mm
rn	0,5 mm
Z_	25
Dx	208
ro	0.6
DE_	191.906
DA_	11.906
SRI	6.16
D_a	193.5
SRE	6.16
DI_	168.094
SRIN	-0.025
yobi	6832NR
SBRG	18
bomp	0

SREX	0.025
KBRG	6101
SREN	-0.025
SDM_	180
SRIX	0.025
mass	1.23
C_conv	48500
r min.	1,1 mm
da max	170,5 mm
ALPHA_	0
Weight	1,23 Kg
da min	166.5
LangID	1
GRS rpm	2600
Da max.	193,5 mm
hidYobi	6832NR
Oil rpm	3200
da min.	166,5 mm
r0 max.	0,6 mm
ra max.	1 mm
hidTable	ecat_NSRDGB
Size (mm)	160x200x20
Prod_Type3	DGBB_SR_NR_OT
Width (mm)	20
Bearing number	6832NR
Bore Diameter (mm)	160
Outer Diameter (mm)	200
(Oil) Lubrication Speed	3 200 r/min
(Grease) Lubrication Speed	2 600 r/min
Basic dynamic load rating (C)	48,5 kN
Basic static load rating	61 kN

(C0)	
------	--