



Bearing No. 6328

D	300 mm
d	140 mm
B	62 mm
C	62 mm
r	4
Z_	8
C0	246
ra	3
fo	13.6
D_	300
B_	62
DI_	172.375
SRI	24.65
DE_	267.625
DA_	47.625
SRE	24.65
D_a	284
KBRG	6101
SRIX	0.08
Noun	Bearing
yobi	6328
SDM_	220
bomp	0
SRIN	-0.08
Bore	5.512 Inch 140 Millimeter
SREX	0.08
mass	18.5
SBRG	3
SREN	-0.08

ALPHA_	0
UNSPSC	31171504
da max	187 mm
LangID	1
r min.	4 mm
C_conv	253000
Weight	18,5 Kg
da min	156
GRS rpm	2000
Oil rpm	2400
hidYobi	6328
da min.	156 mm
Da max.	284 mm
ra max.	3 mm
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Inventory	0.0
Snap Ring	No
Size (mm)	140x300x62
Enclosure	Open
bore type:	Round
Prod_Type3	DGBB_SR_OT
Width (mm)	62
Weight / LBS	48.5
maximum rpm:	2400 rpm
Product Group	B00308
closure type:	Open
Cage Material	Steel
Inch - Metric	Metric
Bearing number	6328
bore diameter:	140 mm
cage material:	Steel Cage

overall width:	62 mm
Keyword String	Ball
finish/coating:	Uncoated
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outer Race Width	2.441 Inch 62 Millimeter
Manufacturer URL	http://www.nskamericas.com
Long Description	140MM Bore; 300MM Outside Diameter; 62MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Outside Diameter	11.811 Inch 300 Millimeter
Weight / Kilogram	18.5
Manufacturer Name	NSK
precision rating:	ABEC1, P0
outside diameter:	300 mm
Internal Clearance	C0-Medium
Bore Diameter (mm)	140
snap ring included:	Without Snap Ring
Outer Diameter (mm)	300
internal clearance:	C0
Minimum Buy Quantity	N/A
row type & fill slot:	Single Row Non-Fill Slot
dynamic load capacity:	253000 N
Harmonized Tariff Code	8482.10.50.68
(Oil) Lubrication Speed	2 400 r/min
Manufacturer Item Number	6328
Internal Special	No

Features	
(Grease) Lubrication Speed	2 000 r/min
Basic static load rating (C0)	246 kN
Basic dynamic load rating (C)	253 kN
Maximum Capacity / Filling Slot	No