



Bearing No. 6830NR

f	1,7 mm
r	1.1
d	150 mm
D	190 mm
B	20 mm
C	20 mm
a	3,3 mm
b	1,9 mm
D2	196,5 mm
B_	20
Cy	4.7
ra	1
C0	58.5
fo	17.1
D_	190
D1	186,8 mm
rn	0,5 mm
Z_	24
Dx	198
ro	0.6
DE_	181.906
DA_	11.906
SRI	6.16
D_a	183.5
SRE	6.16
DI_	158.094
SRIN	-0.025
yobi	6830NR
SBRG	18
bomp	0

SREX	0.025
KBRG	6101
SREN	-0.025
SDM_	170
SRIX	0.025
mass	1.15
C_conv	47500
r min.	1,1 mm
da max	160 mm
ALPHA_	0
Weight	1,15 Kg
da min	156.5
LangID	1
GRS rpm	3200
Da max.	183,5 mm
hidYobi	6830NR
Oil rpm	3800
da min.	156,5 mm
r0 max.	0,6 mm
ra max.	1 mm
hidTable	ecat_NSRDGB
Size (mm)	150x190x20
Prod_Type3	DGBB_SR_NR_OT
Width (mm)	20
Bearing number	6830NR
Bore Diameter (mm)	150
Outer Diameter (mm)	190
(Oil) Lubrication Speed	3 800 r/min
(Grease) Lubrication Speed	3 200 r/min
Basic dynamic load rating (C)	47,5 kN
Basic static load rating	58,5 kN

(C0)	
------	--