



Bearing No. 6832

D	200 mm
d	160 mm
B	20 mm
C	20 mm
f0	16.1
Cr	60.5
Cu	2.20
C0r	56.9
Bore	6.299 Inch 160 Millimeter
Noun	Bearing
Weight	1,45 Kg
r(min)	1.1
UNSPSC	31171504
r min.	1,1 mm
ra max.	1 mm
da(min)	166.5
ra(max)	1
Da max.	193,5 mm
da min.	166,5 mm
Da(max)	193.5
Oil lub.	3400
Category	Single Row Ball Bearing
Snap Ring	No
Size (mm)	160x200x20
Enclosure	Open
Inventory	0.0
Width (mm)	20
Bearing No.	6832
Grease lub.	2900

Weight / LBS	3.197
Product Group	B00308
Cage Material	Steel
Inch - Metric	Metric
Keyword String	Ball
Bearing number	6832
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
(Refer.)Mass(kg)	1.45
Manufacturer URL	http://www.koyousa.com
Long Description	160MM Bore; 200MM Outside Diameter; 20MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Outer Race Width	0.787 Inch 20 Millimeter
Outside Diameter	7.874 Inch 200 Millimeter
Manufacturer Name	KOYO
Weight / US pound	3.19
Internal Clearance	C0-Medium
Bore Diameter (mm)	160
Outer Diameter (mm)	200
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
(Oil) Lubrication Speed	3400 r/min
Internal Special Features	No
(Grease) Lubrication Speed	2900 r/min
Basic static load rating (C0)	56,9 kN

Basic dynamic load rating (C)	48,4 kN
Maximum Capacity / Filling Slot	No